SPEC. / MODEL		H-400A/GA
Cutting Capacity	mm	●400 ■400W x 400H
	in	●16 ■16W x 16H
Bundle Cutting	mm	320W x 230H
	in	12.6W x 9H
Blade size	mm	34W x 1.1t x 4570L
	in	1.34W x 0.042t x 179.92L
Blade Speed	M/min	25,32,42,55,70,80 Variable Speed 20-80 (Opt.)
	F/min	82,105,138,180,230,260 Variable Speed 65-260 (Opt.)
Motor Output	HP	Blade 5 , Hyd. 1 , Coolant 1/8
	KW	Blade 3.75 , Hyd. 0.75 , Coolant 0.1
Shipping Volume (L x W x H)	mm	2520 x 2070 x 2000
	ft	8.27 x 6.79 x 6.56
N.W./G.W.	kg	2100/2320

FEATURE

- 1.Precise cut off length setting.2.Auto head elevation and quick approach control.
- 3. Nesting fixture device for bundle cutting.
- 4.Cutting piece counter with auto-shut-off.
- 5.Multiple stroke counter
- 6.Power-driven blade cleaning brush and coolant cleaning flush hose.
- 7.Carbide and roller blade guides.
- 8. Hydraulic shuttle vice back-jaw feed method.
- 9. Hydraulic blade tension control.
- 10.Work-area light.
- 11. Automatic chip conveyor.
- 12.Two-way open rear vice jaws to ensure precise bar-feed repeatability even in cutting a little bit warped / surface rough works.
- 13.Unique split machine vice allows cutting to within as little as 50 mm of end

**** PLEASE CHECK WITH US ON FEATURES AS WE HAVE 2 MACHINES THAT ARE 2ND HAND THAT SOME FEATURES DO NOT APPLY *******