

METAL GUTTUR BAND SAW





Fast angle stop



Left & right swivel 30° 45° 60°



Bow swivel angle ruler



Bow poisition limit switch



- ▶ Hydraulic cylinder for controlled descent
- ▶ High-capacity band controlled by two-speed motor
- ▶ Accident preventing devices on the fly wheel casing and on the blade
- ▶ Vertical rotation on bolt with adjustable tapered bearings without backlash
- ▶ Band stretching is obtained by electro-mechanical blade tensioner with microswitch
- ▶ Hand switch control available
- ▶ Swivel on both sides
- ▶ Electric coolant system

Item	111		388122
Model			BS-315G
Capacity	Circular	@90°	230mm (9")
	Rectangular	@90°	315×170mm 12.4"×6.7"
	Circular	@60° (Right)	130mm (5")
	Rectangular	@60° (Right)	130×130mm 5"×5",
	Circular	@ 45° (Left & Right)	210mm 8.25"
	Rectangular	@ 45° (Left & Right)	210×170mm (8.25"×6.7")
Blade speed	@50Hz		40/80 MPM
	@60Hz		48/96 MPM
Blade size			2 7 ×0.9×2825mm
Motor			0.75/1.1kW
Drive			Gear
Packing size			163×87×97cm (body) 72×56×60cm (stand)
N.W./G.W.			350/400 kg