



**DIGITAL READ OUT FOR ROLL POSITION**

### STANDARD FEATURES

- Fixed top roller
- Adjustable lower and rear rollers
- Wire grooves in rollers
- Top swing out roller with cam lock handle
- Conical bending device
- Safety trip wire
- Motorised rear pinch roller
- Digital readout for roll position
- Covers over exposed gears
- Roving e-stop with forward & reverse foot

### SPECIFICATIONS

MODEL	1300 x 2.5 mm	1300 x 4.5 mm	1300 x 6.5 mm	1550 x 3.5 mm	2070 x 3.5 mm
Item number	M000133	M000134	M000135	M000136	M000182
Bending length	1300 mm	1300 mm	1300 mm	1550 mm	2070 mm
Banding capacity (mild steel)	2.5 mm	4.5 mm	6.5 mm	3.5 mm	3.5 mm
Minimum rolling diameter	100	130	170	130	140 mm
Roll diameter	90 mm	120 mm	150 mm	120 mm	127 mm
Motor power	1.5 kw	2.2 kw	3 kw	2.5 kw	3 kw
Dimensions	1850 x 750 x 1150 mm	1850 x 750 x 1150 mm	2050 x 800 x 1250 mm	2200 x 800 x 1150 mm	28200 x 870 x 1300 mm
Weight	530 kg	770 kg	930 kg	860 kg	1156 kg