Imsulation Cutting

Complete Machine Tools Pty Ltd



- 4					
	MODEL	R2101	R2102	R2103	R2204
	Working Area	1270mm x	1270mm x	1270 mmx	1600mm x
		1270mm	1800mm	2540mm	3048mm
н		(4' x 4')	(4' x 6')	(4.3' x 8.3')	(5.3' x 10')
	Gantry height	180mm (7")	180mm (7")	180mm (7")	180mm (7")
١	Max. Traverse	30m/min	30m/min	30m/min	30m/min
		(100'/min)	(100'/min)	(100'/min)	(100'/min)
	Max.	20m/min	20m/min	20m/min	20m/min
	Cutting	(87'/min)	(87°/min)	(87°/min)	(87'/min)
	Speed				
	Repeatability	0.025mm	0.025mm	0.025mm	0.025mm
	Accuracy	/0.001"	/0.001"	/0.001"	/0.001"
	Weight (kg)	700	800	9000	1200







LIMAC Knife cutting system includes tangential knife, oscillating knife, kiss cut and creasing wheel, for cutting and creasing soft and semi-rigid materials, for customers in the insulation industry.

LIMAC CNC knife cutting machine body is fully welded fabricated steel allowing the machine to have a high-loading capacity with exceptional stability. The machine frame is stress relieved and precision machined and assembled with high quality linear quide rail ensuring high precision during cutting operations.

The knife cutting can also be integrated with LIMAC router machines so that one machine can cut soft, semi-rigid and hard materials from paper vinyl to wood to aluminum.

LIMAC is the first and as yet the only Chinese CNC router manufacturer in the present market that offers Knife cutting system. With rigid frame, advanced motion control system and a vast range of sizes to choose from, LIMAC knife cutting systems offer more selections to the market and meet the ever-growing market of knife cutting machine.





Industrial controller



123 Bluestone Circuit, Seventeen Mile Rocks, Qld 4073

Email: sales@completemachinetools.com.au

Ph: 07 32793344 Fax: 07 32793364

Internet: www.completemachinetools.com.au